



Apollo Single Inlet Portable and Deck Monitor, 5" Storz Ground Base and Truck mounting flange only

STYLE 3416

Akron Apollo Monitors offer a variety of models with features to fit the ever increasing demands of the fire service with a durable, dependable and stable monitor.

Features

- 360° rotation when mounted in the deck mode, 180° in the portable mode
- Vertical travel from 90° above to 15° below horizontal, with built-in 35° safety stop
- 3" waterway with cast-in turning vanes for efficient flow
- Direct mount - a combination 3" NPT female and 3" flange
- Carbide spikes for extended wear (Spike covers optional)
- Also available as portable only or deck mount only - must specify



Specifications

Type	Portable
Weight	23 lbs (10.4 kg)
Width	13in (330.2mm)
Height	12.69in (322.3mm)
Depth	23.5in (596.9mm)
Material	Pyrolite

Apollo Single Inlet Portable and Deck Monitor, 5" Storz Ground Base and Truck mounting flange only

STYLE 3416



Apollo Single Inlet Portable and Deck Monitor, 5" Storz Ground Base and Truck mounting flange only

STYLE 3416

Apollo Single Inlet Portable Monitor Specifications

Portable ground base monitor with a single 4", 4 1/2", or 5" thread or 4" or 5" storz swivel inlet. The base will have folding legs with no locking mechanism required to keep legs in place. The monitor shall have handwheel elevation control from 90° above to 15° below horizontal with an elevation safety stop at 35° above horizontal; 360° continuous rotation when in the deck mode flowing 1250 gpm and 180° in the portable mode flowing 1000 gpm; horizontal locking mechanism and stops to prevent accidental over-rotation; a full 3" waterway with cast-in turning vanes in each elbow. A 3" NPT & 3" flange combination deck mount shall be supplied (3416 only). The monitor shall also include a pressure gauge, carry handle, grease fittings, safety chain, hardened steel ground spikes and Pyrolite® construction. Deck height not to exceed 12", base weight: 38 1/2 lbs., liftoff weight: 23 lbs.