

INTRODUCING RAZOR *GEN2* (LEVEL II AND IIIA)

INNOVATIVE FEATURES

- Razor-thin construction
- Hybrid build for extended wearability
- Reinforced stopping power


Detailed specifications available upon request

COMMON SPECIAL THREATS


**Armor tested to varying rounds - see preceding pages for exact threats tested*

II

IIIA




5.7 x 28, 40 gr. FNH
SS197SR



5.7 x 28, 40 gr. FNH
SS197SR




9mm, 124 gr. Luger +P
GDHP



5.7 x 28, 27 gr. FNH
SS195LF



.357 SIG, 125 gr. Gold
Dot HP



9mm, 124 gr. Luger +P
GDHP



.44 Rem. Magnum,
240 gr. Hydra-Shok



12 Gauge, 1 oz. Rifled
Slug



Certified to NIJ-0101.06 ballistic requirements

Ultimate concealability - Our thinnest ballistic offering gives officers incredible protection in an extremely light weight solution.

Top tier protection - The Razor armor has been built to match the most strenuous requirements, including the NIJ 0101.06 certification. The level II and IIIA models are capable of stopping some of the most advanced rounds available.

WEAR FACE - THIS SIDE TO BE WORN AGAINST BODY

RAZOR™
BALLISTIC SYSTEM

MODEL: _____
 LAST NAME: _____
 FIRST NAME: _____
 SIZE: _____
 SERIAL #: _____
 LOT #: _____
 LOCATION OF MANUFACTURE: CENTRAL LAKE, MI 49822
 DATE OF MANUFACTURE: _____
 DATE OF ISSUE: _____
 MANUFACTURER'S DECLARED WARRANTY PERIOD: 5 YEARS
 SALES ORDER NUMBER: _____
 THREAT LEVEL: NIJ-0101.06

This model of armor has been determined to comply with NIJ Standard 0101.06 by the NIJ Compliance Testing Program and is listed on the NIJ Compliant Protective List.

WARNING!
This garment is rated ONLY for the ballistic threat level stated above. It is NOT intended to protect against rifle fire or sharp-edged or pointed instruments.

BALLISTIC PAD CARE INSTRUCTIONS
 1. WASH WITH DAMP CLOTH.
 2. DO NOT MACHINE WASH or MACHINE DRY.
 3. DO NOT BLEACH, DRY CLEAN or IRON.

ARMOR EXPRESS™
 ARMOREXPRESS.COM

788 N. W. 88 - PO BOX 516 - CENTRAL LAKE, MI 49822

WEAR FACE - THIS SIDE TO BE WORN AGAINST BODY

RAZOR^{GEN2}

LEVEL II

TECHNICAL SPECIFICATIONS

Model Designation	RZRG2-A-II
Certified to NIJ-0101.06 Threat Level	II
Test ID #	AEX09-001929
NIJ Certified Sizes	C1 - C5
Gender	Neutral
Ballistic Material	Twaron® Flex Woven Aramid & Dyneema® UHMWPE
Pad Cover	Seam-sealed, waterproof Ripstop Nylon

Weight (Areal Density)	0.67 lbs/ft ²
Thickness	0.140 in
V-50 - 9mm	1,822 ft/s
V-50 - .357 Mag.	1,727 ft/s
Certification BFS - 9mm	32.7 mm
Certification BFS - .357 Mag.	35.90 mm
Warranty	5 Years

SPECIAL THREATS*

Weapon	Ammunition
S&W M&P 9mm	Winchester 9mm Luger +P+ 127gr. T-SERIES
.44 REM. MAG	Federal Premium 240gr. HYDRA-SHOK
FN HERSTAL 5.7x28	40gr. Hornady V-Max SS197SR SC
S&W M&P .357 SIG	125gr. GDHP 54234

*Special threat testing conducted in the Armor Express' state-of-the-art Ballistic Research Laboratory using the NIJ-0101.06 shot pattern.

RAZOR^{GEN2}

LEVEL IIIA

TECHNICAL SPECIFICATIONS

Model Designation	RZRG2-A-III A
Certified to NIJ-0101.06 Threat Level	III A
Test ID #	AEX09-002407
NIJ Certified Sizes	C1 - C5
Gender	Neutral
Ballistic Material	Twaron® Flex Woven Aramid & Dyneema® UHMWPE
Pad Cover	Seam-sealed, waterproof Ripstop Nylon

Weight (Areal Density)	0.93 lbs/ft ²
Thickness	0.21 in
V-50 - .357 SIG	1,908 ft/s
V-50 - .44 Mag.	1,746 ft/s
Certification BFS - .357 SIG	30.2 mm
Certification BFS - .44 Mag.	39.5 mm
Warranty	5 Years

Passed DEA protocol dated 12-03-2009

SPECIAL THREATS*

Weapon	Ammunition
BROWNING 12ga.	2 3/4" 1 OZ. FED. LE127 RS
FN HERSTAL 5.7x28	27gr. SS195LF
S&W M&P 9mm	Winchester Ranger 9mm +P+ RA9TA
FN HERSTAL 5.7x28	40gr. SS197SR V-MAX

*Special threat testing conducted in the Armor Express' state-of-the-art Ballistic Research Laboratory using the NIJ-0101.06 shot pattern.

RAZOR *GEN2 FEMALE*

LEVEL II

TECHNICAL SPECIFICATIONS

Model Designation	RZRG2-A-II-FEM
Certified to NIJ-0101.06 Threat Level	II
Test ID #	AEX09-002590
NIJ Certified Sizes	C1 - C5
Gender	Female
Ballistic Material	Twaron® Flex Woven Aramid & Dyneema® UHMWPE
Pad Cover	Seam-sealed, waterproof Ripstop Nylon

Weight (Areal Density)	0.74 lbs/ft ²
Thickness	0.18 in
V-50 - 9mm	1,784 ft/s
V-50 - .357 Mag.	1,680 ft/s
Certification BFS - 9mm	29.8 mm
Certification BFS - .357 Mag.	35.4 mm
Warranty	5 Years

SPECIAL THREATS*

Weapon	Ammunition
FN HERSTAL 5.7x28	SS197SR 40gr. V-MAX
S&W .44 REM. MAG.	240gr. HYDRA-SHOK P44HS1
S&W M&P 9MM	SPEER LE 124gr. GDHP 53617
S&W M&P .357 SIG	SPEER LE 125gr. GDHP 54234

*Special threat testing conducted in the Armor Express' state-of-the-art Ballistic Research Laboratory using the NIJ-0101.06 shot pattern.

RAZOR^{GEN2 FEMALE}

LEVEL IIIA

TECHNICAL SPECIFICATIONS

Model Designation	RZRG2-A-III-A-FEM
Certified to NIJ-0101.06 Threat Level	IIIA
Test ID #	AEX09-002456
NIJ Certified Sizes	C1 - C5
Gender	Female
Ballistic Material	Twaron® Flex Woven Aramid & Dyneema® UHMWPE
Pad Cover	Seam-sealed, waterproof Ripstop Nylon

Weight (Areal Density)	0.97 lbs/ft ²
Thickness	0.23 in
V-50 - .357 SIG	2,020 ft/s
V-50 - .44 Mag.	1,830 ft/s
Certification BFS - .357 SIG	26.8 mm
Certification BFS - .44 Mag.	36.6 mm
Warranty	5 Years

Passed DEA protocol dated 12-03-2009

SPECIAL THREATS*

Weapon	Ammunition
FN HERSTAL 5.7x28	SS197SR 40gr. V-MAX
FN HERSTAL 5.7x28	SS195LF 27gr.
S&W M&P 9MM	Winchester Ranger 9mm +P+ RA9TA
12ga BROWNING	2.75" 1oz Rifled Slug

*Special threat testing conducted in the Armor Express' state-of-the-art Ballistic Research Laboratory using the NIJ-0101.06 shot pattern.