

SUPER VAC



YOUR DEWALT ARSENAL JUST GREW
INTRODUCING SUPER VAC'S NEWEST BATTERY PPV



SUPERVAC  **DEWALT**

TWO NAMES YOU CAN TRUST IN ONE BATTERY FAN

Never in firefighter history has one battery fan worked together with your department's other DeWalt battery-operated tools. Introducing the all-new Super Vac 18" variable-speed battery fan, equipped with dual DeWalt FLEXVOLT® batteries, making this rugged yet compact fan the most swappable PPV interface on the market. Finally, the industry can turn to a fan with a trusted battery name that pairs with 180+ products, including our fan and Super Vac's dependable history.

**PATENT
PENDING**



COMPACT FEATURING A NARROW DESIGN

The V18-BD can even be stored on its side in shelf-style compartments.

180° OF SEPARATION

At Super Vac, we have all the angles of attack covered — and then some. You won't find another battery fan that offers 180 degrees of tilt like the ever-versatile V18-BD. Just this one feature truly sets this battery fan apart from the others.

ONLY 46 LBS. AND STILL, SUPER VAC TOUGH

Curved Handle: Folds into the frame for compact storage; curved design provides higher grip for better ergonomics



Compact, Roll-Cage Frame: Features one of the most compact, lightweight designs among battery PPVs with its aluminum frame design



Stream Shaper Guard: Allows for flexible setback; Air Cone Guard is available by request

Polymer Blade: Minimizes weight; Super Vac's single-piece cast aluminum blade is available by request

Optional Shore Power: 120-240V AC operation is available upon request

Standard Flat-Proof Rubber Tires: Highly maneuverable; easy for tall firefighters to position the fan without bending over



For attic attacks For positive tilt attacks Storage angle For negative tilt attacks For manhole attacks

THE V18-BD PPV WITH DEWALT LITHIUM ION BATTERY



AMCA CERTIFIED UP TO 45 MINUTES OF RUN TIME*

Unlike other brands, we back our numbers with true third-party testing. The ratings below are based on tests in accordance with the Air Movement Control Association (AMCA Standard 240). You'll find this unit proudly listed under Positive Pressure Ventilator at bit.ly/PPV-AMCA-certification.

* Run time based on battery selection

PATENT PENDING

18" Blades - H x W x D: 25.75" x 25.75" x 11.75" - 654mm x 654mm x 298mm

Model	Weight With Batteries	Motor	Setback For Output Rating	Angle For Output Rating	Output
V18-BD	46 lbs 21 kg	Variable-Speed DC with Optional 120-240V AC	15 ft 4.6m	10°	10,840 cfm 18,417 cmh



Battery Options



Standard Battery

Run Time At Max Airflow

DeWalt FLEXVOLT 9.0Ah (2)
(Compatible with all DeWalt
20/60/120V MAX Tools)

35 minutes
(With built-in
battery gauge)



Optional Battery

Run Time At Max Airflow

DeWalt FLEXVOLT 12.0Ah (2)
(Compatible with all DeWalt
20/60/120V MAX Tools)

45 minutes
(With built-in
battery gauge)

Up to 45 minutes run time, depending on battery selection. 120V MAX is based on using 2 DEWALT 60V MAX lithium-ion batteries combined. Optional 120-240V AC operation is available upon request.

Available Accessories

DeWalt FLEXVOLT Batteries, Chargers, Duct, Door Bar, Carry Strap, Mountain Mister, Running Board Mount and High Expansion Foam Adapter.

**5-YEAR
WARRANTY**



800-525-5224

| info@supervac.com

| www.supervac.com

See a Super Vac representative or authorized dealer for further details. All information in this brochure is the latest available at the time of publication. Printed in the USA. 250 0119 ©2018 Super Vac